

Unifi / Advanced Home Security System

Individual products

AI Turret

Overview

Dimensions	Ø118 x 111 mm (Ø4.6 x 4.4")
IR Night Vision	40 m (131 ft)
Face Recognition	Yes
License Plate Recognition	Yes
Smart Detections (People, Vehicles, Animals)	Yes
Resolution	4K
Field of View	H: 109.9°, V: 56.7°, D: 134.1°
Audio	Two-way audio
Weatherproofing	IP66
Tamper Resistance	IK08
Mounting	Ceiling, arm, wall, pendant mount, junction box

G4 Doorbell Pro PoE Kit

Overview

Dimensions	Device: 160.6 x 51.7 x 35.1 mm (6.3 x 2 x 1.4") Wall mount: 159.3 x 50.3 x 17.5 mm (6.3 x 1.9 x 0.7") Wedge: 161.1 x 52.1 x 25.7 mm (6.3 x 2.1 x 1") On-wall mount: 161.1 x 52.1 x 25.75 mm (6.3 x 2.1 x 1")
IR Night Vision	6 m (20 ft)
Smart Detections (People, Vehicles, Animals)	Yes
Resolution	FHD
Field of View	Main camera: H: 138°, V: 114°, D: 155° (LDC On) Main camera: H: 160°, V: 117°, D: 160° (LDC Off) Package camera: H: 97.5°, V: 79.4°, D: 118.2°
Audio	Two-way audio
Weatherproofing	IPX4
Mounting	Wall, wedge (Included) Gang box, junction box (Optional)

Dream Machine Pro

Overview

Dimensions	442.4 x 43.7 x 285.6 mm (17.4 x 1.7 x 11.2")
UniFi Application Suite	
Network	Yes
Protect	Yes
Access	Yes
Talk	Yes
Connect	Yes
Managed UniFi Devices	100+
Managed Cameras	(24) HD (14) 2K (8) 4K
Simultaneous Users Connected	1,000+
Default WAN Ports	(1) 10G SFP+ (1) GbE RJ45
LAN Ports	(1) 10G SFP+ (8) GbE RJ45
IDS/IPS Throughput	3.5 Gbps
Form Factor	Rack mount (1U)
Redundancy	Shadow Mode (VRRP) Gateway Failover DC Power Backup

Standard 16 PoE

Overview

Dimensions	442 x 200 x 44 mm (17.4 x 7.9 x 1.7")
Port Layout	
1 GbE RJ45	16 (8 PoE+)
1G SFP	2
Max. PoE Output	Up to PoE+
Total PoE Availability	42W
Form Factor	Rack mount (1U)

Enterprise 3.5" HDD, 8 TB

Mechanical

Dimensions	147 x 101.9 x 26.1 mm (5.75 x 4 x 1")
Hard disk form factor	3.5-inch
Weight	720 g (1.6 lb)

Hardware

Capacity	8 TB
Management interface	SATA 6 Gb/s
Rotation speed	7200 RPM
Power method	5V/12V input
Workload rating	550 TB/year
Mean time between failure (MTBF)	2,000,000 h
Ambient operating temperature	5 to 60° C (41 to 140° F)
Ambient operating humidity	5 to 90% noncondensing

Power Backup

Dimensions	442.4 x 325.6 x 43.7 mm (17.4 x 12.8 x 1.7")
Weight	Without mount brackets : 5.5 kg (12.1 lb) With mount brackets: 5.6 kg (12.3 lb)
Enclosure material	SGCC steel